



VSP 977 V2
7" Video Doorphone kit

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunications, Professional Audio and Automation.

Featured specifications

OUTDOOR UNIT

- Self adaptive IR supplement
- CMOS camera
- 120 degrees wide camera angle
- ABS housing
- Unlocking controlling

INDOOR UNIT

- 7" Color TFT screen (1024x600)
- Handsfree video intercom communication
- Supports monitoring the outdoor unit
- Remote unlocking
- Convenient installation and easy operation
- 4-wire connection

GENERAL

- Maximum Configuration: 2 Cameras / 4 Monitors

OUTDOOR UNIT

VIDEO PARAMETERS

Camera:	1/3" CMOS
Resolution:	2Mpx
Video frame rate:	PAL:25fps

AUDIO PARAMETERS

Audio input:	Built-in Microphone
Audio output:	Built-in Loudspeaker
Audio quality:	Noise Suppression and Echo Cancellation

LIGHT SUPPLEMENT

Light supplement mode:	Photosensitive IR Supplement, IR Range: ≤ 4 Meters
------------------------	--

DEVICE INTERFACES

Six-wire interface:	Four-wire Interface (1-ch Audio, 1-ch Video, 1-ch Grounding, 1-ch Power) Two-wire Interface 1-ch Lock+, 1ch Lock -)
---------------------	--

GENERAL

Material:	ABS housing and bracket
Working temperature:	-20° C to +50° C
Working humidity:	10%to 90%
Size(with rain cover):	52mm x 129mm x 35mm
Size(without rain cover):	52mm x 129mm x 29 mm

INDOOR UNIT

DISPLAY PARAMETERS

Display screen:	7 inch color TFT screen
Display resolution:	1024x600
Operation method:	Physical button

AUDIO PARAMETERS

Audio input:	Built-in Microphone
Audio output:	Built-in Loudspeaker
Audio quality:	Noise Suppression and Echo Cancellation

DEVICE INTERFACES

Four-wire interface:	Four-wire Interface (1-ch Audio, 1-ch Video, 1-ch Grounding, 1-ch Power)
----------------------	--

GENERAL

Power supply:	DC15V1A
Power consumption:	Static state <3W Working state <10W
Working temperature:	-20° C to+50° C
Working humidity:	10%to 90%
Dimension(L x W x H):	182(W)x133(H)x19.5(D)mm

