



## VSP 987

7" Video Doorphone kit

*Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunications, Professional Audio and Automation.*

### Featured specifications

#### OUTDOOR UNIT

- Self adaptive white light supplement
- CMOS camera
- 70 degrees wide camera angle
- Stainless steel camera body
- Unlocking controlling
- Multiple door controller ACC 978 to connect 2 outdoor cameras optional (not included)

#### INDOOR UNIT

- 7" Color TFT screen (800x480)
- Handsfree video intercom communication
- Supports monitoring the outdoor unit
- Remote unlocking
- Convenient installation and easy operation
- 4-wire connection

#### GENERAL

- Maximum Configuration: 2 Cameras / 2 Monitors



#### OUTDOOR UNIT

##### VIDEO PARAMETERS

Camera:	1/3" CMOS
Resolution:	700TVL
Video frame rate:	PAL:25fps

##### AUDIO PARAMETERS

Audio input:	Built-in Microphone
Audio output:	Built-in Loudspeaker
Audio quality:	Noise Suppression and Echo Cancellation

##### LIGHT SUPPLEMENT

Light supplement mode:	White LED. Range: ≤ 4 Meters
------------------------	------------------------------

##### DEVICE INTERFACES

Six-wire interface:	Four-wire Interface (1-ch Audio, 1-ch Video, 1-ch Grounding, 1-ch Power) Two-wire Interface (1-ch Lock+, 1ch Lock -)
---------------------	---

#### GENERAL

Material:	Stainless steel camera body, ABS rain cover
Working temperature:	-20° C to +50° C
Working humidity:	10%to 90%
Size (with rain cover):	64mm x 153mm x 45mm
Size (without rain cover):	57mm x 148mm x 28 mm

#### INDOOR UNIT

##### DISPLAY PARAMETERS

Display screen:	7 inch color TFT screen
Display resolution:	800x480
Operation method:	Physical button

##### AUDIO PARAMETERS

Audio input:	Built-in Microphone
Audio output:	Built-in Loudspeaker
Audio quality:	Noise Suppression and Echo Cancellation

##### DEVICE INTERFACES

Four-wire interface:	Four-wire Interface (1-ch Audio, 1-ch Video, 1-ch Grounding, 1-ch Power)
----------------------	--

#### GENERAL

Power supply:	DC12V1A
Power consumption:	≤5W
Working temperature:	-20° C to+50° C
Working humidity:	10%to 90%
Dimension (L x W x H):	182(W)x133(H)x19.5(D)mm