



## PRO 9043IP-CH

IP Wall Mount Video Intercom Station

*Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.*

### Featured specifications

- 4.3 inch color TFT LCD Display
- Front panel Aluminium
- Camera Resolution 2Mpx automatic LED white light.
- View angle FOV 115° (H)/ 75° (V)/ 125° (D)
- Door Entry: MF 13,56Mhz & EM 125Khz card, PIN code
- Built-in digital audio
- 3 Output Relay for door opener
- IP / IK Rating: IP65, IK07
- Surface Mount Installation
- PoE (IEEE802.3af, Power-over-Ethernet) or DC 12V/2A
- Complies with SIP standard for easy integration in every SIP PBX
- Induction loop for hearing impaired
- Braille dot for visually impaired
- Tamper alarm
- ControlHub mobile app supported

Physical Property	
System:	Linux
Front Panel:	Aluminium
Display	4.3 inch TFT LCD / 480 x 272 Resolution
Button:	Mechanical
Power Supply:	PoE (802.3af) or DC 12V/2A
Standby Power:	1.5W
Rated Power:	9W
Camera:	2MP, CMOS
IR Sensor:	Support
Wiegand Port:	Support
Ethernet Port:	1 x RJ45, 10/100 Mbps adaptive
Door Entry:	MF (13.56Mhz) & EM (125Khz) card, PIN Code.
Reset Button:	1
RS485 Port:	1
Relay Out:	3
Input:	4
IP/IK Rating:	IP65 / IK07
Installation:	Surface Mounting
Surface Mounting Dimentions:	295 x 133 x 43 mm
Working Temperature:	-40°C to +55°C
Storage Temperature:	-40°C to +70°C
Working Humidity:	10% to 90% (non-condensing)
Audio & Video	
Audio Codec:	G.711 / Echo Cancellation
DTMF:	RFC2833
Microphone:	Built-in microphone
Speaker:	8 ohms/ 1W
Video Codec:	H.264
Camera:	Resolution 1280x720 / FOV 115° (H) / 75° (V) / 125° (D)
Max Image Transfer Rate:	720p-25fps
Light Compensation:	Led White light
Network	
Protocol:	Onvif, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP
Mobile App:	ControlHub

