



IPL 2401IP/28-5MPX

5 Megapixel

IP Dome Camera

Designed for professional outdoor applications, where the ULTRA HD resolution, and the 24 hs reliable recording are needed.

Featured specifications

- H.265+
- 5 Megapixel
- Siera CLOUD
- Dual Streaming
- 2.8mm Fixed Lens
- PoE
- SIERA DDNS
- ONVIF
- Outdoor IP66
- Metal Case
- 40 mts IR Range
- Encrypted Communication
- Auto Frame Rate adapter according to the network bandwidth
- Mobile phone and Webserver viewer
- Siera CMS for 128 cameras (Win / MAC)

| | |
|------------------------------------|--|
| Sensor: | 1/3" / 5Mpx |
| Lens: | 2.8mm Fixed Lens |
| Electronic Shutter: | 1/25s~1/100,000s |
| Illumination min.: | 0,08 Lux |
| Image resolution supported: | 2592*1920 |
| Frame Rate: | 1~15fps |
| Video Compression: | H.265+ |
| Video Bite Rate: | 32K~16Mbps adjustable |
| Privacy masking: | 4 zones |
| Day/Night Function: | IR CUT |
| IR Range: | 40mts |
| Video Settings: | Saturation, Brightness, Shutter, Contrast, AGC, Iris, Backlight, Flicker, Mirror, IR |
| Data Stream: | Video and data |
| Ethernet: | 1-ch 10/100M, RJ45 |
| Main Processor: | High performance microprocessor |
| Operation System: | Embedded Linux |
| Security: | Password protection, multi-level user |
| View: | Webserver, CMS and Mobile through Siera iSMS 5.0 |
| Compatibility: | ONVIF |
| Smartphone app: | iSMS 5.0 (available in iOS and Android) |
| Network Protocol: | TCP/IP/HTTP/RTSP/FTP/PPPoE/RTCP/SMTP/DHCP/DDNS NTP/UPnP/SNMP |
| Working Temperature: | -20° - 55°C |
| Working Humidity: | <95% |
| Power: | DC12V / PoE |
| Consumption: | 10W / 0,5A |
| Dimension: | 150 x 120 mm |
| Weight: | 1,0 Kg |

