



PRO 9001IP-CH
IP Wall Mount Video Intercom Station

Sierra manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- Outdoor/Indoor Villa Entrance Door
- Front panel Plastic
- Camera Resolution 2Mpx with WDR mode
- View angle FOV 110° (H)/ 60°(V)/ 125° (D)
- Door Entry: Indoor Monitor or Mobile App
- Motion Detection
- MF Card Reader, Wifi and Bluetooth
- 1 Output Relay for door opener
- IP65
- Surface Mount Installation
- PoE (IEEE802.3af, Power-over-Ethernet) or DC 12V/2A
- Complies with SIP standard for easy integration in every SIP PBX
- 110° Wide-angle 2MP HD camera with automatic lighting
- TF Card Slot for storage
- Compact Design
- Tamper alarm
- ControlHub mobile app supported

Physical Property	
System:	Linux
Front Panel:	Plastic
Power Supply:	PoE (802.3af) or DC 12V/2A
Indicator Light:	3
Camera:	2MP, CMOS, WDR
IR Sensor:	Support
Wiegand Port:	Support
Ethernet Port:	1 x RJ45, 10/100 Mbps adaptive
Door Entry:	MF (13.56Mhz) card
Reset Button:	1
RS485 Port:	1
Relay Out:	1
Input:	2
IP Rating:	IP65
Installation:	Surface Mounting
Surface Mounting Dimentions:	130 x 50 x 28 mm
Working Temperature:	-40°C to +55°C
Storage Temperature:	-40°C to +70°C
Working Humidity:	10% to 90% (non-condensing)
Audio & Video	
Audio Codec:	G.711 / Echo Cancellation
DTMF:	RFC2833
Microphone:	Built-in microphone
Speaker:	Built-in speaker
Video Codec:	H.264
Camera:	Resolution 1920x1080 / FOV 110° (H) / 60° (V) / 125° (D)
Max Image Transfer Rate Light:	1080p-25fps
Compensation:	Led White light
Network	
Protocol:	SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP
Mobile App:	ControlHub

