



PRO 9043IP-FR-CH

IP Wall Mount Video Intercom Station

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 4.3 inch TFT LCD
- Front panel Aluminium
- Camera Resolution 2Mpx with WDR mode
- View angle FOV 120° (H)/ 80°(V)/ 130°(D)
- Door Entry: Face, MF13,56Mhz & EM125Khz card, PIN code
- Facial Recognition (No distortion)
- RAM 1Gb / ROM 8Gb
- 3 Output Relay for door opener
- IP / IK Rating: IP65, IK07
- Surface Mount Installation
- PoE+ (IEEE802.3at, Power-over-Ethernet) or DC 12V/2A
- Complies with SIP standard for easy integration in every SIP PBX
- 120° Wide-angle 2MP HD camera with automatic lighting
- 2 MP camera with WDR mode
- Braille dot for visually impaired
- Induction loop for hearing impaired
- Tamper alarm
- ControlHub mobile app supported

Physical Property

System:	Android
Front Panel:	Aluminium
Display	4.3 inch TFT LCD / 480 x 272 Resolution
Button:	Mechanical
Power Supply:	PoE+ (802.3at) or DC 12V/2A
Standby Power:	8W
Rated Power:	16W
Camera:	2MP, CMOS, WDR
IR Sensor:	Support
Wiegand Port:	Support
Ethernet Port:	1 x RJ45, 10/100 Mbps adaptive
Door Entry:	Face, MF (13.56Mhz) & EM(125Khz) card, PIN Code
Reset Button:	1
RS485 Port:	1
Relay Out:	3
Input:	4
IP/IK Rating:	IP65 / IK07
Installation:	Surface Mounting
Surface Mounting Dimentions:	295 x 133 x 43 mm
Working Temperature:	-40°C to +55°C
Storage Temperature:	-40°C to +70°C
Working Humidity:	10% to 90% (non-condensing)
Audio & Video	
Audio Codec:	G.711 / Echo Cancellation
DTMF:	RFC2833
Microphone:	Built-in microphone
Speaker:	8 ohms/ 1W
Video Codec:	H.264
Camera:	Resolution 1920x1080 / FOV 120° (H) / 80° (V) / 130° (D)
Max Image Transfer Rate:	1080p-25fps
Light Compensation:	Led White light
Network	
Protocol:	Onvif, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP
Mobile App:	ControlHub

