



PRO 9080IP-FR-CH

IP Wall Mount Video Intercom Station

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 8 inch color IPS LCD Capacitive touch screen
- Front panel Aluminum
- Camera Resolution 2Mpx automatic LED white light.
- View angle FOV 120° (H)/ 75°(V)/ 131° (D)
- Door Entry: Facial, MF13,56Mhz & EM125Khz card, PIN code
- Built-in digital audio
- 3 Output Relay for door opener
- IP / IK Rating: IP65, IK08
- Surface Mount Installation
- PoE+ (IEEE802.3at, Power-over-Ethernet) or DC 12V/3A
- Complies with SIP standard for easy integration in every SIP PBX
- 120° Wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20.000 users, 20.000 faces and 60.000 cards
- Tamper alarm
- ControlHub mobile app supported

Physical Property

System:	Android
Front Panel:	Aluminium
Display	8 inch IPS LCD / 1280 x 800 Resolution
Button:	Touch
Power Supply:	PoE+ (802.3at) or DC 12V/3A
Standby Power:	8W
Rated Power:	16W
Camera:	2MP, CMOS, WDR
IR Sensor:	Support
Wiegand Port:	Support
Ethernet Port:	1 x RJ45, 10/100 Mbps adaptive
Door Entry:	Face, MF(13.56Mhz) & EM(125Khz) card, PIN Code
Reset Button:	1
RS485 Port:	1
Relay Out:	3
Input:	4
IP/IK Rating:	IP65 / IK08
Installation:	Surface Mounting
Surface Mounting Dimintions:	140 x 300 x 41.8 mm
Working Temperature:	-40°C to +55°C
Storage Temperature:	-40°C to +70°C
Working Humidity:	10% to 90% (non-condensing)
Audio & Video	
Audio Codec:	G.711 / Echo Cancellation
DTMF:	RFC2833
Microphone:	Built-in microphone
Speaker:	8 ohms/ 1W
Video Codec:	H.264
Camera:	Resolution 1920x1080 / FOV 120° (H) / 75° (V) / 131° (D)
Max Image Transfer Rate:	1080p-25fps
Light Compensation:	Led White light
Network	
Protocol:	Onvif, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP
Mobile App:	ControlHub

