

Passive Video Balun AHD/ CVI/ TVI/ CBVS UTP 101HD

Features:

-) Compatible with all: HDCVI, HDTVI, AHD, CBVS
-) Up to 450m for 720P CVI
-) Up to 250m for 1080P/3MP CVI
-) Up to 200m for 4MP/5MP CVI
-) Up to 250m for 1080P/3MP TVI
-) Up to 450m for 720P TVI
-) Up to 400m for 720P/1080P AHD
-) Up to 200m for 1080P/3MP/4MP/5MP AHD
-) Up to 500m for CBVS Cameras.
-) NTSC, PAL and SECAM video formats.
-) No power required.
-) 60dB cross talk and noise immunity.
-) Built-in transient suppression protection.
-) Innovative combinable design.



Technical Specifications:

Frequency response: DC to 60Mhz.
Attenuation: 0.5dB Type.
CMRR: 60dB.
Surge Protection: 4KV / ESD: 8KV
Connectors: Male BNC and "Press-Fit" terminal blocks.
Impedance: BNC: 75 ohms / Terminal: 100 ohms.
Working Temperature: -10°C to +70°C.
Storage Temperature: -30°C to +70°C.
Humidity: 0 to 95%.
Dimension: 39 x 17 x 19mm (excluding connectors).
Material: ABS Plastic
Body color: Black
Net Weight: 50g

Data subject to change without prior notice.
Some products may not be available in all countries.

www.sieraelectronics.com

Siera
ALWAYS RELIABLE®